

Cisco Nexus 31128PQ Switch

Product Overview

The Cisco Nexus[®] 31128PQ Switch is a dense, high-performance Layer 2 and 3, 10- and 40-Gbps switch that is a member of the Cisco Nexus 3100 switches. The Nexus 3100 switches are the second-generation Cisco Nexus 3000 series switches and offer improved port density, scalability, and features compared to the first-generation switches. The Cisco Nexus 31128PQ comes in a compact two-rack-unit (2RU) form factor and runs the industry-leading Cisco[®] NX-OS Software operating system, providing customers comprehensive features and functions that are widely deployed. It supports both forward and reverse (port side exhaust and port side intake) airflow schemes with AC and DC power inputs. The Cisco Nexus 31128PQ is well suited for data centers that require a cost-effective, power-efficient line-rate Layer 2 and 3 access or leaf switch.

The Cisco Nexus 31128PQ (Figure 1) is a 10-Gbps Enhanced Small Form-Factor Pluggable (SFP+) and 40-Gbps Quad Small Form-Factor Pluggable (QSFP+) based switch with 96 SFP+ ports and 8 QSFP+ ports.

Figure 1. Cisco Nexus 31128PQ Switch



Main Benefits

The Cisco Nexus 31128PQ provides the following main benefits:

- Wire-rate Layer 2 and 3 switching on all ports¹
 - Layer 2 and 3 switching of up to 2.5 terabits per second (Tbps) and up to 1.4 Billion packets per second (bps) is provided in a compact 2RU form-factor switch.
- High availability
 - Virtual PortChannel (vPC) technology provides Layer 2 multipathing through the elimination of Spanning Tree Protocol and enables fully utilized bisectional bandwidth and simplified Layer 2 logical topologies without the need to change the existing management and deployment models.
 - The 64-way equal-cost multipath (ECMP) routing enables the use of Layer 3 fat-tree designs and allows organizations to prevent network bottlenecks, increase resiliency, and add capacity with little network disruption.
 - Hot swappable power-supply units (PSUs) and fans.
- High Performance
 - The Cisco Nexus 31128PQ delivers low nominal latency, which enables customers to implement high-performance infrastructure for high-frequency trading (HFT) and high-performance computing (HPC) workloads.

¹ Wire-rate on all ports for packets >200bytes.

- Purpose-built Cisco NX-OS operating system with comprehensive, proven innovations
 - PowerOn Auto Provisioning (POAP) enables touchless bootup and configuration of the switch, drastically reducing provisioning time.
 - Cisco Embedded Event Manager (EEM) and Python scripting enable automation and remote operations in the data center.
 - Advanced buffer monitoring reports real-time buffer utilization per port and per queue, which allows organizations to monitor traffic bursts and application traffic patterns.
 - EtherAnalyzer is a built-in packet analyzer for monitoring and troubleshooting control-plane traffic and is based on the popular Wireshark open source network protocol analyzer.
 - Precision Time Protocol (PTP; IEEE 1588) provides accurate clock synchronization and improved data correlation with network captures and system events.
 - Complete Layer 3 unicast and multicast routing protocol suites are supported, including Border Gateway Protocol (BGP), Open Shortest Path First (OSPF), Enhanced Interior Gateway Routing Protocol (EIGRP), Routing Information Protocol Version 2 (RIPv2), Protocol Independent Multicast sparse mode (PIM-SM), Source-Specific Multicast (SSM), and Multicast Source Discovery Protocol (MSDP).

Configuration

The Cisco Nexus 31128PQ has the following configuration:

- 96 fixed 10 Gigabit Ethernet SFP+ ports
- 8 fixed 40 Gigabit Ethernet QSFP+ ports
- Locator, Status and Environment LEDs
- Dual redundant power supplies
- Redundant (1+1) fans (2 rotors per fan)
- One 10/100/1000-Mbps management port
- One RS-232 serial console port
- Two USB ports

Both forward (port-side exhaust) and reversed (port-side intake) airflow schemes are supported.

Transceiver and Cabling Options

The Cisco Nexus 31128PQ has 8 QSFP+ ports. QSFP+ technology allows a smooth transition from 10 to 40 Gigabit Ethernet infrastructures in data centers. This switch supports both fiber and copper cabling solutions for these two modes. For low-cost cabling, copper-based 40-Gbps Twinax cables can be used, and for longer cable reaches, short-reach optical transceivers are excellent.

For details about the optics modules available and the minimum software release required for each supported optics module, please visit:

http://www.cisco.com/en/US/products/hw/modules/ps5455/products_device_support_tables_list.html.

For more information about the transceiver types, see

http://www.cisco.com/en/US/products/hw/modules/ps5455/prod_module_series_home.html.

Cisco NX-OS Software Overview

Cisco NX-OS is a data center-class operating system built with modularity, resiliency, and serviceability at its foundation. Cisco NX-OS helps ensure continuous availability and sets the standard for mission-critical data center environments. The self-healing and highly modular design of Cisco NX-OS makes zero-impact operations a reality and enables exceptional operation flexibility.

Focused on the requirements of the data center, Cisco NX-OS provides a robust and comprehensive feature set that meets the networking requirements of present and future data centers. With an XML interface and a command-line interface (CLI) like that of Cisco IOS® Software, Cisco NX-OS provides state-of-the-art implementations of relevant networking standards as well as a variety of true data center-class Cisco innovations.

Cisco NX-OS Software Benefits

Table 1 summarizes that benefits that Cisco NX-OS offers.

Table 1. Benefits of Cisco NX-OS Software

Feature	Benefit
Common software throughout the data center: Cisco NX-OS runs on all Cisco data center switch platforms (Cisco Nexus 9000, 7000, 6000, 5000, 4000, 3000 and 1000V Series Switches and Cisco Nexus 2000 Series Fabric Extenders).	<ul style="list-style-type: none"> • Simplification of data center operating environment • End-to-end Cisco Nexus and Cisco NX-OS fabric • No retraining necessary for data center engineering and operations teams
Software compatibility: Cisco NX-OS interoperates with Cisco products running any variant of Cisco IOS Software and also with any networking OS that conforms to the networking standards listed as supported in this data sheet.	<ul style="list-style-type: none"> • Transparent operation with existing network infrastructure • Open standards • No compatibility concerns
Modular software design: Cisco NX-OS is designed to support distributed multithreaded processing. Cisco NX-OS modular processes are instantiated on demand, each in a separate protected memory space. Thus, processes are started and system resources allocated only when a feature is enabled. The modular processes are governed by a real-time preemptive scheduler that helps ensure timely processing of critical functions.	<ul style="list-style-type: none"> • Robust software • Fault tolerance • Increased scalability • Increased network availability
Troubleshooting and diagnostics: Cisco NX-OS is built with unique serviceability functions to enable network operators to take early action based on network trends and events, enhancing network planning and improving network operations center (NOC) and vendor response times. Cisco Smart Call Home and Cisco Online Health Management System (OHMS) are some of the features that enhance the serviceability of Cisco NX-OS.	<ul style="list-style-type: none"> • Quick problem isolation and resolution • Continuous system monitoring and proactive notifications • Improved productivity of operations teams
Ease of management: Cisco NX-OS provides a programmatic XML interface based on the NETCONF industry standard. The Cisco NX-OS XML interface provides a consistent API for devices. Cisco NX-OS also provides support for Simple Network Management Protocol (SNMP) Versions 1, 2, and 3 MIBs. In addition NX-API and Linux Bash are now supported.	<ul style="list-style-type: none"> • Rapid development and creation of tools for enhanced management • Comprehensive SNMP MIB support for efficient remote monitoring
Role-based access control (RBAC): With RBAC, Cisco NX-OS enables administrators to limit access to switch operations by assigning roles to users. Administrators can customize access and restrict it to the users who require it.	<ul style="list-style-type: none"> • Tight access control mechanism based on user roles • Improved network device security • Reduction in network problems arising from human errors

Cisco NX-OS Software Packages for Cisco Nexus 31128PQ

The Cisco NX-OS Software packages available with the Cisco Nexus 31128PQ offer flexibility and a comprehensive feature set as well as consistency with Cisco Nexus access switches. The default system software has a comprehensive Layer 2 feature set with robust security and management features. To enable Layer 3 IP unicast and multicast routing functions, additional licenses need to be installed. Table 2 summarizes the software packages. See Table 4 later in this document for a complete list of software features.

Table 2. Cisco NX-OS Software Packages Available for Cisco Nexus 31128PQ

Software Package	Features Supported
System default: Base license (N3K-BAS1K9) included; no purchase necessary	<ul style="list-style-type: none"> Comprehensive Layer 2 feature set: VLAN, IEEE 802.1Q Trunking, vPC, Link Aggregation Control Protocol (LACP), Unidirectional Link Detection (UDLD; standard and aggressive), Multiple Spanning Tree Protocol (MSTP), Rapid Spanning Tree Protocol (RSTP), spanning-tree guards, and Transparent VLAN Trunk Protocol (TVTP) Security: Authentication, authorization, and accounting (AAA); access control lists (ACLs), Dynamic Host Configuration Protocol (DHCP) snooping, storm control, private VLAN (PVLAN), and configurable Control-Plane Policing (CoPP) Management features: Cisco Data Center Network Manager (DCNM) support, console, Secure Shell Version 2 (SSHv2) access, Cisco Discovery Protocol, SNMP, and syslog Layer 3 IP routing: inter-VLAN routing (IVR), static routes, RIPv2, ACLs, OSPFv2, EIGRP stub, Hot Standby Router Protocol (HSRP), Virtual Router Redundancy Protocol (VRRP), and Unicast Reverse-Path Forwarding (uRPF) Multicast: PIM SM, SSM, and MSDP
LAN Enterprise license (N3K-LAN1K9)	<ul style="list-style-type: none"> Advanced Layer 3 IP routing: BGP, and Virtual Route Forwarding lite (VRF-lite) VXLAN Policy-Based Routing (PBR)

Cisco Data Center Network Manager

The Cisco Nexus 31128PQ is supported in Cisco DCNM. Cisco DCNM is designed for hardware platforms enabled for Cisco NX-OS, which consist of the Cisco Nexus Family of products. Cisco DCNM is a Cisco management solution that increases overall data center infrastructure uptime and reliability, hence improving business continuity. Focused on the management requirements of the data center network, Cisco DCNM provides a robust framework and comprehensive feature set that meets the routing, switching, and storage administration needs of present and future data centers. In particular, Cisco DCNM automates the provisioning process, proactively monitors the LAN by detecting performance degradation, secures the network, and streamlines the diagnosis of dysfunctional network elements.

Product Specifications

Table 3 lists the specifications for the Cisco Nexus 31128PQ, Table 4 lists software features, and Table 5 lists management standards and support.

Table 3. Specifications

Description	Specification	
Physical	<ul style="list-style-type: none"> 2RU fixed form-factor switch 8 QSFP+ ports 96 SFP+ ports 2 redundant power supplies 2 redundant (1+1) fans (2 rotors per fan) Management, console, and 2 USB flash-memory ports 	
Performance	<ul style="list-style-type: none"> 2.5 Tbps switching capacity Forwarding rate up to 1.4 bpps Line-rate traffic throughput (both Layer 2 and 3) on all ports Configurable maximum transmission units (MTUs) of up to 9216 bytes (jumbo frames) 	
Hardware tables and scalability	Number of MAC addresses	288,000
	Number of VLANs	4096
	Number of spanning-tree instances	<ul style="list-style-type: none"> RSTP: 512 MSTP: 64
	Number of access control list (ACL) entries	4000 ingress 1000 egress

Description	Specification	
	Routing table	<ul style="list-style-type: none"> • 16,000 prefixes and 16,000 host entries* • 8000 multicast routes*
	Number of EtherChannels	64 (with vPC)
	Number of ports per EtherChannel	16
	Buffer size	12 MB shared
	Boot flash memory	64 GB SSD
Power	Frequency	50 to 60 Hz
	Power supply types	<ul style="list-style-type: none"> • AC (forward and reversed airflow) • DC (forward and reversed airflow)
	Typical operating power	<ul style="list-style-type: none"> • 190 watts (W) with Twinax at 100% load; 2 PSUs • 248 watts (W) with 10G SR + 40G SR4 optics at 100% load; 2 PSUs
	Maximum power	396 watts (W)
	AC PSUs <ul style="list-style-type: none"> • Input voltage • Frequency • Efficiency 	<ul style="list-style-type: none"> • 100 to 240 VAC • 50 to 60 Hz • 89 to 91% at 220V
	DC PSUs <ul style="list-style-type: none"> • Input voltage • Maximum current • Efficiency 	<ul style="list-style-type: none"> • -40 to -72 VDC • 8.25A • 85 to 88%
	Power-supply efficiency	89 to 91% at 220V
	Typical heat dissipation	<ul style="list-style-type: none"> • 648 BTU/hr (with Twinax at 50% load) • 846 BTU/hr (with SR and SR4 optics at 50% load)
	Maximum heat dissipation	1351 BTU/hr
Cooling	<ul style="list-style-type: none"> • Forward and reversed airflow schemes <ul style="list-style-type: none"> ◦ Forward airflow: Port-side exhaust (air enters through fan tray and power supplies and exits through ports); supported with AC and DC power supplies ◦ Reversed airflow: Port-side intake (air enters through ports and exits through fan tray and power supplies); supported with AC power supply only • Redundant fans • Hot swappable (must swap within 1 minute) 	
Sound	Measured sound power (maximum)	
	<ul style="list-style-type: none"> • Fan speed: 40% duty cycle • Fan speed: 70% duty cycle • Fan speed: 100% duty cycle 	<ul style="list-style-type: none"> • 66.1 dBA • 70.6 dBA • 76.9 dBA
Environment	Dimensions (height x width x depth)	3.84 x 17.41 x 22.32 in. (8.84 x 44.2 x 56.6 cm)
	Weight	22.2 lb (10.1 kg)
	Operating temperature	32 to 122°F (0 to 50°C)
	Storage temperature	-40 to 158°F (-40 to 70°C)
	Operating relative humidity	<ul style="list-style-type: none"> • 10 to 85% noncondensing • Up to 5 days at maximum (85%) humidity • Recommend ASHRAE data center environment
	Storage relative humidity	5 to 95% noncondensing
	Altitude	0 to 10,000 ft (0 to 3000m)

* Please refer to Cisco Nexus 3000 Series Verified Scalability Guide documentation for exact scalability numbers validated on for specific software releases:
http://www.cisco.com/en/US/products/ps11541/products_installation_and_configuration_guides_list.html.

Table 4. Software Features

Description	Specification
Layer 2	<ul style="list-style-type: none"> • Layer 2 switch ports and VLAN trunks • IEEE 802.1Q VLAN encapsulation • Support for up to 4096 VLANs • Rapid Per-VLAN Spanning Tree Plus (PVRST+) (IEEE 802.1w compatible) • MSTP (IEEE 802.1s): 64 instances • Spanning Tree PortFast • Spanning Tree Root Guard • Spanning Tree Bridge Assurance • Cisco EtherChannel technology (up to 16 ports per EtherChannel) • LACP: IEEE 802.3ad • vPC • Advanced PortChannel hashing based on Layer 2, 3, and 4 information • Jumbo frames on all ports (up to 9216 bytes) • Storm control (unicast, multicast, and broadcast) • Private VLANs • NvGRE Entropy • Resilient Hashing
Layer 3	<ul style="list-style-type: none"> • Layer 3 interfaces: Routed ports on interfaces, switch virtual interfaces (SVIs), PortChannels, and subinterfaces (total: 1024) • 64-way ECMP • 4000 ingress and 1000 egress ACL entries • Routing protocols: Static, RIPv2, EIGRP, OSPFv2, and BGP • Bidirectional Flow Detection (BFD) for BGP • HSRP and VRRP • ACL: Routed ACL with Layer 3 and 4 options to match ingress and egress ACLs • VRF: VRF-lite (IP VPN), VRF-aware unicast (BGP, OSPF, and RIP), and VRF-aware multicast • uRPF with ACL; strict and loose modes • Jumbo frame support (up to 9216 bytes) • Advanced BGP features including BGP add-path for eBGP and iBGP, remove-private-as enhancements and eBGP next hop unchanged • IP-in-IP Tunnel support • VXLAN
Multicast	<p>Multicast: PIMv2, PIM-SM, and PIM-SSM</p> <p>Bootstrap router (BSR), Automatic Rendezvous Point (Auto-RP) and Static RP</p> <p>Multicast Source Discovery Protocol (MSDP) and Anycast RP</p> <p>Internet Group Management Protocol (IGMP) Versions 2 and 3</p>
Quality of service (QoS)	<p>Layer 2 IEEE 802.1p (class of service [CoS])</p> <p>8 unicast and 8 multicast hardware queues per port</p> <p>Per-port QoS configuration</p> <p>CoS trust</p> <p>Port-based CoS assignment</p> <p>Modular QoS CLI (MQC) compliance</p> <p>ACL-based QoS classification (Layers 2, 3, and 4)</p> <p>MQC CoS marking</p> <p>Differentiated services code point (DSCP) marking</p> <p>Weighted Random Early Detection (WRED)</p> <p>CoS-based egress queuing</p> <p>Egress strict-priority queuing</p> <p>Egress port-based scheduling: Weighted Round-Robin (WRR)</p> <p>Explicit Congestion Notification (ECN)</p> <p>Priority Flow Control (with 3 no-drop queues and 1 default queue with strict priority scheduling between queues)</p> <p>Policy Based Routing (PBR)</p>

Description	Specification
Security	<ul style="list-style-type: none"> ● Ingress ACLs (standard and extended) on Ethernet ● Standard and extended Layer 3 to 4 ACLs: IPv4, Internet Control Message Protocol (ICMP), TCP, User Datagram Protocol (UDP), etc. ● VLAN-based ACLs (VACLs) ● Port-based ACLs (PACLs) ● Named ACLs ● ACLs on virtual terminals (vty) ● DHCP snooping with Option 82 ● Port number in DHCP Option82 ● DHCP relay ● Dynamic Address Resolution Protocol (ARP) inspection ● Configurable CoPP ● SPAN with ACL Filtering
Management	<ul style="list-style-type: none"> ● Switch management using 10/100/1000-Mbps management or console ports ● CLI-based console to provide detailed out-of-band management ● In-band switch management ● Locator and beacon LEDs ● Port-based locator and beacon LEDs ● Configurable CoPP ● Configuration rollback ● SSHv2 ● Telnet ● AAA ● AAA with RBAC ● RADIUS ● TACACS+ ● Syslog ● Syslog generation on system resources (for example, FIB tables) ● Embedded packet analyzer ● SNMP v1, v2, and v3 ● Enhanced SNMP MIB support ● XML (NETCONF) support ● Remote monitoring (RMON) ● Advanced Encryption Standard (AES) for management traffic ● Unified username and passwords across CLI and SNMP ● Microsoft Challenge Handshake Authentication Protocol (MS-CHAP) ● Digital certificates for management between switch and RADIUS server ● Cisco Discovery Protocol Versions 1 and 2 ● RBAC ● Cisco SPAN on physical, PortChannel, VLAN, and Fibre Channel interfaces ● ERSPAN ● Ingress and egress packet counters per interface ● PTP (IEEE 1588) boundary clock ● Network Time Protocol (NTP) ● Cisco OHMS ● Comprehensive bootup diagnostic tests ● Cisco Call Home ● Cisco DCNM ● Advanced buffer monitoring ● Linux Bash ● NX-API

Table 5. Management and Standards Support

Description	Specification	
MIB support	<p>Generic MIBs</p> <ul style="list-style-type: none"> • SNMPv2-SMI • CISCO-SMI • SNMPv2-TM • SNMPv2-TC • IANA-ADDRESS-FAMILY-NUMBERS-MIB • IANAifType-MIB • IANAiprouteprotocol-MIB • HCNUM-TC • CISCO-TC • SNMPv2-MIB • SNMP-COMMUNITY-MIB • SNMP-FRAMEWORK-MIB • SNMP-NOTIFICATION-MIB • SNMP-TARGET-MIB • SNMP-USER-BASED-SM-MIB • SNMP-VIEW-BASED-ACM-MIB • CISCO-SNMP-VACM-EXT-MIB • CISCO-CLASS-BASED-QOS-MIB <p>Ethernet MIBs</p> <ul style="list-style-type: none"> • CISCO-VLAN-MEMBERSHIP-MIB • LLDP-MIB • IP-MULTICAST-MIB <p>Configuration MIBs</p> <ul style="list-style-type: none"> • ENTITY-MIB • IF-MIB • CISCO-ENTITY-EXT-MIB • CISCO-ENTITY-FRU-CONTROL-MIB • CISCO-ENTITY-SENSOR-MIB • CISCO-SYSTEM-MIB • CISCO-SYSTEM-EXT-MIB • CISCO-IP-IF-MIB • CISCO-IF-EXTENSION-MIB • CISCO-NTP-MIB • CISCO-IMAGE-MIB • CISCO-IMAGE-UPGRADE-MIB 	<p>Monitoring MIBs</p> <ul style="list-style-type: none"> • NOTIFICATION-LOG-MIB • CISCO-SYSLOG-EXT-MIB • CISCO-PROCESS-MIB • RMON-MIB • CISCO-RMON-CONFIG-MIB • CISCO-HC-ALARM-MIB <p>Security MIBs</p> <ul style="list-style-type: none"> • CISCO-AAA-SERVER-MIB • CISCO-AAA-SERVER-EXT-MIB • CISCO-COMMON-ROLES-MIB • CISCO-COMMON-MGMT-MIB • CISCO-SECURE-SHELL-MIB <p>Miscellaneous MIBs</p> <ul style="list-style-type: none"> • CISCO-LICENSE-MGR-MIB • CISCO-FEATURE-CONTROL-MIB • CISCO-CDP-MIB • CISCO-RF-MIB <p>Layer 3 and Routing MIBs</p> <ul style="list-style-type: none"> • UDP-MIB • TCP-MIB • OSPF-MIB • BGP4-MIB • CISCO-HSRP-MIB
Standards	<ul style="list-style-type: none"> • IEEE 802.1D: Spanning Tree Protocol • IEEE 802.1p: CoS Prioritization • IEEE 802.1Q: VLAN Tagging • IEEE 802.1s: Multiple VLAN Instances of Spanning Tree Protocol • IEEE 802.1w: Rapid Reconfiguration of Spanning Tree Protocol • IEEE 802.3z: Gigabit Ethernet • IEEE 802.3ad: Link Aggregation Control Protocol (LACP) • IEEE 802.3ae: 10 Gigabit Ethernet • IEEE 802.1ab: LLDP • IEEE 1588-2008: Precision Time Protocol (Boundary Clock) 	

Description	Specification
RFC	<p data-bbox="548 325 592 348">BGP</p> <ul data-bbox="565 359 1206 785" style="list-style-type: none"> <li data-bbox="565 359 906 380">● RFC 1997: BGP Communities Attribute <li data-bbox="565 390 1206 411">● RFC 2385: Protection of BGP Sessions with the TCP MD5 Signature Option <li data-bbox="565 422 889 443">● RFC 2439: BGP Route Flap Damping <li data-bbox="565 453 1084 474">● RFC 2519: A Framework for Inter-Domain Route Aggregation <li data-bbox="565 485 1003 506">● RFC 2545: Use of BGPv4 Multiprotocol Extensions <li data-bbox="565 516 971 537">● RFC 2858: Multiprotocol Extensions for BGPv4 <li data-bbox="565 548 1052 569">● RFC 3065: Autonomous System Confederations for BGP <li data-bbox="565 579 1003 600">● RFC 3392: Capabilities Advertisement with BGPv4 <li data-bbox="565 611 735 632">● RFC 4271: BGPv4 <li data-bbox="565 642 1133 663">● RFC 4273: BGPv4 MIB: Definitions of Managed Objects for BGPv4 <li data-bbox="565 674 857 695">● RFC 4456: BGP Route Reflection <li data-bbox="565 705 1068 726">● RFC 4486: Subcodes for BGP Cease Notification Message <li data-bbox="565 737 987 758">● RFC 4724: Graceful Restart Mechanism for BGP <li data-bbox="565 768 1068 789">● RFC 4893: BGP Support for Four-Octet AS Number Space <li data-bbox="565 800 1003 821">● RFC 5549: BGP Ipv4 NLRIs with an IPv6 next hop <p data-bbox="548 800 605 821">OSPF</p> <ul data-bbox="565 831 1157 989" style="list-style-type: none"> <li data-bbox="565 831 816 852">● RFC 2328: OSPF Version 2 <li data-bbox="565 863 1068 884">● RFC 3101: OSPF Not-So-Stubby-Area (NSSA) Option <li data-bbox="565 894 963 915">● RFC 3137: OSPF Stub Router Advertisement <li data-bbox="565 926 1157 947">● RFC 3509: Alternative Implementations of OSPF Area Border Routers <li data-bbox="565 957 873 978">● RFC 3623: Graceful OSPF Restart <li data-bbox="565 989 849 1010">● RFC 4750: OSPF Version 2 MIB <p data-bbox="548 999 589 1020">RIP</p> <ul data-bbox="565 1031 1003 1598" style="list-style-type: none"> <li data-bbox="565 1031 857 1052">● RFC 1724: RIPv2 MIB Extension <li data-bbox="565 1062 898 1083">● RFC 2082: RIPv2 MD5 Authentication <li data-bbox="565 1094 792 1115">● RFC 2453: RIP Version 2 <li data-bbox="565 1125 678 1146">● IP Services <li data-bbox="565 1157 922 1178">● RFC 768: User Datagram Protocol (UDP) <li data-bbox="565 1188 963 1209">● RFC 783: Trivial File Transfer Protocol (TFTP) <li data-bbox="565 1220 686 1241">● RFC 791: IP <li data-bbox="565 1251 719 1272">● RFC 792: ICMP <li data-bbox="565 1283 711 1304">● RFC 793: TCP <li data-bbox="565 1314 711 1335">● RFC 826: ARP <li data-bbox="565 1346 719 1367">● RFC 854: Telnet <li data-bbox="565 1377 703 1398">● RFC 959: FTP <li data-bbox="565 1409 768 1430">● RFC 1027: Proxy ARP <li data-bbox="565 1440 1003 1461">● RFC 1305: Network Time Protocol (NTP) Version 3 <li data-bbox="565 1472 995 1493">● RFC 1519: Classless Interdomain Routing (CIDR) <li data-bbox="565 1503 784 1524">● RFC 1542: BootP Relay <li data-bbox="565 1535 979 1556">● RFC 1591: Domain Name System (DNS) Client <li data-bbox="565 1566 784 1587">● RFC 1812: IPv4 Routers <li data-bbox="565 1598 792 1619">● RFC 2131: DHCP Helper <li data-bbox="565 1629 727 1650">● RFC 2338: VRRP <p data-bbox="548 1619 654 1640">IP Multicast</p> <ul data-bbox="565 1650 1417 1892" style="list-style-type: none"> <li data-bbox="565 1650 1068 1671">● RFC 2236: Internet Group Management Protocol, version 2 <li data-bbox="565 1682 1068 1703">● RFC 3376: Internet Group Management Protocol, Version 3 <li data-bbox="565 1713 1182 1734">● RFC 3446: Anycast Rendezvous Point Mechanism Using PIM and MSDP <li data-bbox="565 1745 849 1766">● RFC 3569: An Overview of SSM <li data-bbox="565 1776 1044 1797">● RFC 3618: Multicast Source Discovery Protocol (MSDP) <li data-bbox="565 1808 1417 1829">● RFC 4601: Protocol Independent Multicast - Sparse Mode (PIM-SM): Protocol Specification (Revised) <li data-bbox="565 1839 930 1860">● RFC 4607: Source-Specific Multicast for IP <li data-bbox="565 1871 865 1892">● RFC 4610: Anycast-RP using PIM <li data-bbox="565 1902 816 1923">● RFC 5132: IP Multicast MIB

Software Requirements

Cisco Nexus 3100 Series Switches are supported by Cisco NX-OS Software Release 7.0(3)I2(1) and later. Cisco NX-OS interoperates with any networking OS, including Cisco IOS Software, that conforms to the networking standards mentioned in this data sheet.

Regulatory Standards Compliance

Table 6 summarizes regulatory standards compliance for the Cisco Nexus 3100 Series.

Table 6. Regulatory Standards Compliance: Safety and EMC

Specification	Description
Regulatory compliance	<ul style="list-style-type: none"> • Products should comply with CE Markings per directives 2004/108/EC and 2006/95/EC
Safety	<ul style="list-style-type: none"> • UL 60950-1 Second Edition • CAN/CSA-C22.2 No. 60950-1 Second Edition • EN 60950-1 Second Edition • IEC 60950-1 Second Edition • AS/NZS 60950-1 • GB4943
EMC: Emissions	<ul style="list-style-type: none"> • 47CFR Part 15 (CFR 47) Class A • AS/NZS CISPR22 Class A • CISPR22 Class A • EN55022 Class A • ICES003 Class A • VCCI Class A • EN61000-3-2 • EN61000-3-3 • KN22 Class A • CNS13438 Class A
EMC: Immunity	<ul style="list-style-type: none"> • EN55024 • CISPR24 • EN300386 • KN24
RoHS	The product is RoHS 5 compliant except for lead press-fit connectors

Ordering Information

Table 7 provides ordering information for the Cisco Nexus 31128PQ.

Table 7. Ordering Information

Part Number	Description
Chassis	
N3K-C31128PQ-10GE	Nexus 31128PQ, 96 SFP+ ports, 8 QSFP+ ports, 2RU switch
N9K-C9300-FAN3-B	N9K Fan Module, Forward airflow (port side exhaust)
N9K-C9300-FAN3	N9K Fan Module, Reversed airflow (port side intake)
N9K-PAC-650W-B	N9K 650W AC Power Supply, Forward airflow (port side exhaust)
N9K-PAC-650W	N9K 650W AC Power Supply, Reversed airflow (port side intake)
UCSC-PSU-930WDC	N9K 930W DC Power Supply, Forward airflow (port side exhaust)
UCS-PSU-6332-DC	N9K 930W DC Power Supply, Reversed airflow (port side intake)

Part Number	Description
Software Licenses	
N3K-LAN1K9	Nexus 3000 Layer 3 LAN Enterprise License
Spares	
N9K-C9300-FAN3-B=	N9K Fan Module, Forward airflow (port side exhaust), Spare
N9K-C9300-FAN3=	N9K Fan Module, Reversed airflow (port side intake), Spare
N9K-PAC-650W-B=	N9K 650W AC Power Supply, Forward airflow (port side exhaust), Spare
N9K-PAC-650W=	N9K 650W AC Power Supply, Reversed airflow (port side intake), Spare
UCSC-PSU-930WDC=	N9K 930W DC Power Supply, Forward airflow (port side exhaust), Spare
UCS-PSU-6332-DC=	N9K 930W DC Power Supply, Reversed airflow (port side intake), Spare
N9K-C9300-ACK	N9K Accessory Kit

Service and Support

Cisco offers a wide range of services to help accelerate your success in deploying and optimizing the Cisco Nexus 3100 Series in your data center. The innovative Cisco Services offerings are delivered through a unique combination of people, processes, tools, and partners and are focused on helping you increase operation efficiency and improve your data center network. Cisco Advanced Services uses an architecture-led approach to help you align your data center infrastructure with your business goals and achieve long-term value.

Cisco SMARTnet[®] Service helps you resolve mission-critical problems with direct access at any time to Cisco network experts and award-winning resources.

With this service, you can take advantage of the Cisco Smart Call Home service capability, which offers proactive diagnostics and real-time alerts on your Cisco Nexus 3100 Series Switches. Spanning the entire network lifecycle, Cisco Services helps increase investment protection, optimize network operations, support migration operations, and strengthen your IT expertise.

For More Information

For more information, please visit <http://www.cisco.com/go/nexus3000>.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)